



VIEW "A"

HYDRAULIC SYMBOL



SPECIFICATION

1. 최고사용압력 : 250 kgf/cm²
2. 최대유량 : 65 l/min
3. CRACKING 압력 : 0.5 kgf/cm²
4. 면적비 – 6.5:1
5. ② TORQUE 범위 : 2,700~3,000 kgf.cm
6. 형식기호설명 :

LPC – 06 – 05 –10
- 10 : DESIGN 번호
- 05 : CRACKING 압력 : 0.5 kgf/cm²
- 06 : 호칭경 : PF3/4
- LPC : 기본형식 : LINE PILOT CHECK V/V



SECTION S-S



ITEM	DESCRIPTION	DRAWING NO	MATERIAL	Q'TY	REMARKS
11	NAME PLATE	8842642		1	
10	O-RING			1	AS568-018A
9	O-RING			1	AS568-028A
8	PISTON SPRING	8842621		1	
7	PISTON	8831249		1	
6	CHECK SPRING	8842620		1	
5	CHECK	8842619		1	
4	막음 PLUG	8842618		1	PF3/4
3	O-RING			1	AS568-129B
2	CHECK PLUG	8831248		1	M45xP2.0
1	BODY	8831247		1	
ITEM	DESCRIPTION	DRAWING NO	MATERIAL	Q'TY	REMARKS



PF1/4 PORT DETAIL



PF3/4 PORT DETAIL

NO.	DATE	REVISIONS	Q'TY	CHARGE	APPROVED
6	. . .				
5	. . .				
4	. . .				
3	. . .				
2	. . .				
1	. . .				

주식회사 득인기공 DUKIN INDUSTRIES CO., LTD.

SCALE	N/S	DATE	2011.04
DIM	mm		
PLANT	STANDARD	FACILITY	LINE PI-CHECK VALVE
TITLE	LPC-06-05 (ASS'Y)		
REFERENCE DWG. NO.		REV	
DRAWING NO.	8831246	REV	

SIGN / DATE — DESIGNED — CHECKED — REVIEWED — APPROVED — DISKETTE NO.

A3(420x297) (주) 득인기공